

Drain body The Universal DN 100, St. St. grat, Backwater protect



Article information

Item no.: 27621

GTIN: 4026092007839

Price group: 10

Advantages

- Flexible installation: vertically adjustable upper section rotatable
- Integrated backwater protection
- vertically adjustable

Description

The polymer drain body is equipped with a removable backwater valve with two backwater flaps, one hand-lockable emergency closure and a sludge bucket. The drain body also has two inlets DN 50 and one inlet DN 70 with blind plug. Material:

PΡ

Variant

Contents of sludge trap: yes Emergency closure: yes

Waterproof flange: Pre-assembled at the factory

Mechanical backwater flaps: 2

General characteristics

Colour: black
Standard: EN 1253
Nominal size (DN): 100
Outer diameter (OD): 110 mm

Type of wastewater: without sewage Installation situation: floor slab installation Delivery state: installation-ready

Backwater protection: Type 5

Dimensions

Net weight: 3,23 kg
Gross weight: 3,55 kg
Cutout dimension, width: 320 mm
Cutout dimension, length: 400 mm
Installation depth: 216 - 266 mm

Vertical adjustment: vertically adjustable upper section



Length:380 mmWidth:300 mmPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Tank/drain body

System: lateral

Coverage features

Type of cover: Slotted cover

Cover material: Stainless steel 14301

Colour of cover: silver

Load class: K 3 (EN 1253-1)

Grating material: 187 mm
Grid size, width: 187 mm
Grid size, height: 4 mm
Contents of sludge trap: yes
Odour trap: included

Cover

Grating material: 187 mm
Grid size, width: 187 mm
Grid size, height: 4 mm