


## Universal Plus basement drain vertical, with odour trap





## Article information

Item no.: 29103

GTIN: 4026092096963

Price group: 10

## **Advantages**

- Sustainable due to use of recycled material
- Inlets above the floor slab, no penetration required
- Vertical outlet for easy installation and easy access to the main drainage pipe

## Description

In combination with an upper section, the polymer Universal Plus drain body is used for drainage of non-faecal wastewater and is equipped with a removable odour trap and a sludge bucket. Including temporary protective cover. The drain is pressure-waterproof up to 0.6 bar (MFPA Leipzig tested) and radon-tight (IAF Radioökologie GmbH tested).

Variant

Contents of sludge trap: yes
Waterproof flange: without
Sealing water height: 60 mm

General characteristics

Colour: black
Standard: EN 1253
Nominal size (DN): 100

Type of wastewater: without sewage Installation situation: floor slab installation

**Dimensions** 

Net weight:1,73 kgGross weight:2,22 kgDiameter:235 mmCutout dimension, width:310 mm



Cutout dimension, length: 310 mm

Vertical adjustment: vertically adjustable upper section

Height: 270 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Outlet nominal size (OD): 110 mm
Outlet nominal size (DN): 100 mm
System: vertical

Coverage features

Contents of sludge trap: yes
Odour trap: included